

### **PRODUCT DESCRIPTION**

KOPRO-30 extrusion is designed to build universal interior light fixtures. This extrusion directs the light beam at an angle of 30° so you can achieve the effect of mild accent illumination and avoid glare. It is to be mounted in corners (e.g. bodies of furniture, cabinets, where ceiling meets wall, shop windows).

The extrusion can also serve as a wall lamp fixture. The KOPRO-30 extrusion can be mounted with screws or bolts (suitable for a particular substrate) screwed into the walls of the extrusion which are not intended for LEDs. Holes for the bolts or screws should be drilled in places designated by the lines inside the extrusion. In drywall ceilings, the profile can be fixed using GP mounting springs. The KOPRO-30 extrusion can also be mounted using mounting adhesives.

After the extrusion has been mounted, a shallow 'tray' is formed which can be used to route the power cables. The profile can be additionally equipped with two 10 mm (0.39") wide LED strips or one LED strip with a width of no more than 20 mm (7.87'). There are two types of covers and 4 types of end caps which are dedicated for the KOPRO-30 extrusion.

- Covers in two shapes
- Easy wiring
- Numerous assembly options

Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	




## TECHNICAL SPECIFICATION

B7890ANODA_1	Silver anodized	39.4"
B7890ANODA_2	Silver anodized	78.75"
B7890ANODA_3	Silver anodized	118.11"




Specification sheet - KOPRO-30 Extrusion ref. number B7890ANODA





#### **RELATED PRODUCTS**

#### COVERS



## END CAPS



Ref: 24176



Ref: 24177



Ref: 24178



Ref: 24179

#### ACCESSORIES



Ref: 00293



Ref: 42203







Ref: 42205



Specification sheet - KOPRO-30 Extrusion ref. number B7890ANODA

# **COUPLERS** - connection methods for profiles



L135



L90PW



T90



L135PW



L90PZ



X135




L135PZ



T135L







T135R